

REVISIONS

DATE REMARKS


- - --


## CENTRAL HIGH SCHOOL PROPOSED TEMPORARY LIBRARY 5A-B VICORP EST., C'STED. RR #2 KINGSHILL 00850 ST. CROIX, U.S.V.I.


— CLIENT INFORMATION

DEPARTMENT OF EDUCATION
DIVISION OF MAINTENANCE
1111D LA GRANDE PRINCESS
CHRISTIANSTED, ST. CROIX.
U.S.V.I. 00821

DRAWN BY	DRAWING NO
W. MATTHEW	
CHECKED BY	DATE
ALAN FLEMING	08/19/20
APPROVED BY	SHEET NO
JAMES BENIER. P.E.	C1







DOOR SCHEDULE				
TAG	SIZE (WxH)	DESCRIPTION	REMARKS	
<b>D-1</b>	6'-0" x 6'-8"	COMMERCIAL GRADE 18 GUAGE, WITH COMMERCIAL HARDWARE	6'-4" x 6'-10" MASONRY OPENING	
D-2	3'-0" x 6'-8"	COMMERCIAL GRADE 18 GUAGE, WITH COMMERCIAL HARDWARE	3'-4" x 6'-10" MASONRY OPENING	

FINISH SCHEDULE							
NUM	ROOM NAME	FLOOR	BASE	WALLS	CEILING	CABINET	COMMENTS
-	LIBRARY	VINYL TILES WITH COVE BASE	-	PAINT	PAINT	-	-
-	-	-	-	_	-	-	_

WINDOW SCHEDULE					
TAG	SIZE (WxH)	DESCRIPTION	REMARKS		
<b>W-1</b>	4'-0" x 3'-0"	ALUMINUM FRAME WITH IMPACT GLASS	HIGH WINDOWS		


PLEASE VERIFY ALL FIELD MEASUREMENTS

NOTE: Contractor shall field verify all dimensions elevation, quantity and conditions prior to final bid submission


#### CONSTRUCTION NOTES

(ALL SHEETS)

- 1. ALL EXTERIOR WOOD AND TRIM SHALL BE WOLMANIZED TREATED.
- 2. ALL WINDOW AND DOOR HEAD HEIGHTS SHALL BE 6'-8" (U.O.N.) ABOVE FINISHED FLOOR. ALL
- 3. 5/8" INTERIOR & 7/8" EXTERIOR FOR PLASTER FINISHES.










FLOOR SLAB 6" WITH **EPOXY** LANDING DETAIL SCALE: 1" = 1'-0"

B





### A ELECTRICAL PANEL LOAD DISTRIBUTION CENTER - 1 150 AMPERE CIRCUIT BREAKER PANEL 120 / 240 VOLTS 3 PHASE



### ELECTRICAL LEGEND

**SLAVE WIRING** 

110 VOLT DUPLEX OUTLET	$\langle \# \rangle$	CIRCUIT TAG & NUMBER
COUNTERTOP OUTLET	CECI	
220 VOLT OUTLET	GFCI	GROUND FAULT CIRCUIT INTERRUPT
SINGLE POLE SWITCH	WP	WATERPROOF
3WAYS SWITCH		FLUORESCENT LIGHT
TELEPHONE JACK		
TELEVISION JACK		ELECTRICAL PANEL
SMOKE DETECTOR		
(INTERCONNECTED & HARD WIRED)		5 TON SPLIT A.C. (3 PHASE)
SECURITY SPOTLIGHT	***	
LIGHT FIXTURE	Ì	FIRE EXTINGUISHER
WALL MOUNTED LIGHT FIXTURE		FIREMAN SWITCH
PRIMARY WIRING (3 WIRE/ GROUND)		
	COUNTERTOP OUTLET 220 VOLT OUTLET SINGLE POLE SWITCH 3WAYS SWITCH TELEPHONE JACK TELEVISION JACK SMOKE DETECTOR (INTERCONNECTED & HARD WIRED) SECURITY SPOTLIGHT LIGHT FIXTURE WALL MOUNTED LIGHT FIXTURE	COUNTERTOP OUTLET 220 VOLT OUTLET SINGLE POLE SWITCH WP 3WAYS SWITCH TELEPHONE JACK TELEVISION JACK SMOKE DETECTOR (INTERCONNECTED & HARD WIRED) SECURITY SPOTLIGHT LIGHT FIXTURE WALL MOUNTED LIGHT FIXTURE

# OF EDUCATION ALAINTENANCE NDE PRINCESS ED, ST. CROIX. JAMES BENIER. P.E. JAMES BENIER. P.E.

### DEPARTMENT OF EDUCA DIVISION OF MAINTENA 1111D LA GRANDE PRINCE


## L D


### ELECTRICAL NOTES


- 1. ALL THE ELECTRICAL WORKS SHALL BE COMPLETED IN STRICT ACCORDANCE WITH THE LATE EDISON OF THE N.E.C.
- 2. THE ELECTRICIAN SHALL OBTAIN ALL PERMITS AND PAY FEES RELATED TO HIS WORK. ALL WIRING SHALL BE #12 COPPER OR LARGER.
- 3. ALUMINUM WIRING NOT ACCEPTABLE.
- 4. RECEPTACLES OUTLETS IN HABITABLE ROOMS SHALL BE INSTALLED SO THAT NO POINT MEASURED HORIZONTALLY ALONG THE FLOOR LINE IN ANY WALL SPACE IS MORE THAN 6 FT FROM A RECEPTACLE OUTLET. A RECEPTACLE SHALL BE INSTALLED IN EACH SPACE 2 FT OR MORE IN WIDTH.
- 5. WIRE TYPE AWG IS PREFERRED, ALTHOUGH OTHERS ARE ACCEPTABLE.
- 6. ALL WIRING SPLICES BE MADE USING 3M ELECTRICAL SPRING CONNECTOR OR EQUAL "TWIST-ONS"TO CORRECT SIZE. WIRE TAPED OR TWISTED OR NOT ACCEPTABLE.
- 7. ALL CONDUITS INSTALLED IN CONCRETE OR MASONRY SHALL BE RIGID NON-METALLIC TYPE (P.V.C.) ALL OUTLETS AND SWITCH BOXES SHALL BE NON-METALIC TYPE.
- 8. GROUNDING CONDUCTOR SHALL BE CONNECTED TO NEUTRAL CONNECTOR AT THE SERVICE ENTRANCE ONLY. CERTAIN EXCEPTIONS AS PERMITTED BY THE N.E.C. SHALL BE PERMITTED.
- 9. ELECTRICAL SERVICE SHALL BE 120-240 VOLTS, SINGLE PHASE, 60 CYCLES, 3 WIRE CONNECTION. SERVICE SHALL BEGIN AT POINT OF ATTACHMENTS OF OVERHEAD SERVICE DROP CABLE.
- 10. ELECTRICAL SYSTEM LAYOUT INDICATED ON DRAWINGS ARE GENERALLY DIAGRAMMATIC AND LOCATION OF OUTLETS AND EQUIPMENT ARE APPROXIMATE; ROUTING RACEWAY AND LOCATION OF OUTLET AND EQUIPMENTS SHALL BE GOVERNED BY STRUCTURAL CONDITIONS AND OBSTRUCTIONS
- 11. ALL BRANCH WIRING SHALL BE COPPER THHN SIZED FOR IT'S APPLICATION AND SHALL BE IN RIGID NON-METALLIC TYPE (P.V.C) CONDUIT.
- 12. PROVIDE SURGE PROTECTOR @ PANEL BOX.
- 13. ALL SMOKE DETECTORS 'SHALL BE HARD WIRED AND INTERCONNECTED WITH BATTERY BACK-UP.
- 14. GROUND FAULT INTERRUPT (GFI) RECEPTACLES SHALL BE USED FOR ALL KITCHEN AND BATHROOM RECEPTACLES OR RECEPTACLES WITHIN 60 INCHES ANY WATER SOURCES.
- 15. ALL EXTERIOR ELECTRICAL FIXTURES OR RECEPTACLES SHALL BE WATERPROOF.

PROJECT TITLE———PROJECT TITLE—
CENTRAL HIGH SCHOOL
PROPOSED TEMPORARY LIBRAR
5A-B VICORP EST., C'STED.
PR. #2 KINGSHII I 00850

DATE REMARKS
-- --







DIVISION OF MAINTENANCE
1111D LA GRANDE PRINCESS
CHRISTIANSTED, ST. CROIX.
U.S.V.I. 00821

DEPARTMENT

ANCHOR BOLT @ 4'-0" O.C.

POURED

CONCRETE

(4) #4 REBAR

VERTICAL IN

COLUMN

**CORNER** 

COLUMN

- #4 REBAR @

@ CORNER

COLUMN

8"x8"x16"

**BLOCK** 

CONCRETE

18" O.C. WRAPPED

AROUND VERTICAL

HORIZONTALLY

SCHOOL
ARY LIBRA
C'STED.
L 00850 PROPOSED TEMPORA 5A-B VICORP EST.,